

5032 SERIES TOTAL DYNAMIC HEAD / FLOW PER MINUTE EFFLUENT

| MODEL | | 1/2 HP 4 STAGE | | 3/4 HP 6 STAGE | | 1 HP 7 STAGE | | 1-1/2 HP 10 STAGE | |
|----------------|------|-------------------|--------|-------------------|--------|-----------------|--------|----------------------|--------|
| | | Gal. | Liters | Gal. | Liters | Gal. | Liters | Gal. | Liters |
| 20 | 6.1 | 32.9 | 124.5 | 35.9 | 135.9 | 37.5 | 141.9 | 37.4 | 141.6 |
| 40 | 12.2 | 30.1 | 113.9 | 34.2 | 129.5 | 35.8 | 135.5 | 36.3 | 137.4 |
| 60 | 18.3 | 26.4 | 99.9 | 32.3 | 122.3 | 34.1 | 129 | 35.2 | 133.3 |
| 80 | 24.4 | 22.3 | 84.4 | 30.4 | 115 | 32.3 | 122.3 | 34.3 | 129.8 |
| 100 | 30.5 | 16.1 | 60.9 | 28 | 106 | 30.4 | 115.1 | 32.9 | 124.5 |
| 120 | 36.6 | 5 | 18.9 | 25.4 | 96.1 | 28.3 | 107.1 | 31.8 | 120.4 |
| 140 | 42.7 | -- | -- | 22.3 | 84.4 | 26 | 98.4 | 30.3 | 114.7 |
| 160 | 48.8 | -- | -- | 18.7 | 70.8 | 23.4 | 88.6 | 28.9 | 109.4 |
| 180 | 54.9 | -- | -- | 13.7 | 51.9 | 20.5 | 77.6 | 27.3 | 103.3 |
| 200 | 61 | -- | -- | -- | -- | 17.2 | 65.1 | 25.8 | 97.7 |
| 220 | 67.1 | -- | -- | -- | -- | 7.1 | 26.9 | 24.1 | 91.2 |
| 240 | 73.2 | -- | -- | -- | -- | -- | -- | 22.0 | 83.3 |
| 260 | 79.3 | -- | -- | -- | -- | -- | -- | 19.5 | 73.8 |
| 280 | 85.3 | -- | -- | -- | -- | -- | -- | 16.5 | 62.5 |
| 300 | 91.4 | -- | -- | -- | -- | -- | -- | 12.4 | 46.9 |
| Shut-off Head: | | 122 Ft. (37.2m) | | 190 Ft. (57.9m) | | 222 Ft. (67.7m) | | 311 Ft. (94.8m) | |