

5030 SERIES TOTAL DYNAMIC HEAD/FLOW PER MINUTE EFFLUENT

MODEL		1/2 HP 5 STAGE		1/2 HP 7 STAGE		3/4 HP 10 STAGE		1 HP 13 STAGE	
		Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters
Feet	Meters								
40	12.2	14.4	54.5	14.5	54.9	-	-	-	-
80	24.4	12.1	45.8	13.1	49.6	14.1	53.4	14.6	55.3
120	36.6	9.4	35.6	11.6	43.9	13.0	49.2	13.7	51.9
160	48.8	5.5	20.8	9.6	36.3	11.8	44.7	12.8	48.5
200	61	--	--	7.1	26.9	10.6	40.1	12.0	45.4
240	73.2	--	--	2.0	7.6	9.3	35.2	11.0	41.6
280	85.3	--	--	--	--	7.6	28.8	9.9	37.5
320	97.5	--	--	--	--	5.6	21.2	8.7	32.9
360	109.7	--	--	--	--	3.2	12.1	7.3	27.6
400	121.9	--	--	--	--	--	--	5.6	21.2
440	134.1	--	--	--	--	--	--	3.7	14.0
480	146.3	--	--	--	--	--	--	1.8	6.8
Shut-off Head:		177 ft. (54.0m)		241 ft. (73.6m)		401 ft. (122.2m)		504 ft. (153.6m)	