

3.20.090 CI 0031 0823 Supersedes 0123

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347 SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961 Tel: (502) 778-2731 • 1 (800) 928-PUMP

Visit our website: zoellerpumps.com

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

TECHNICAL DATA CENTRIFUGAL STEP SYSTEMS

The Centrifugal STEP System is designed to be an economical and reliable solution to an onsite or low pressure sewer pumping requirement. When effluent must be pumped uphill, the Centrifugal STEP System does the job without the added cost of an extra pump tank or chamber. It is a lowcost, high-quality option for onsite enhanced flow systems, repairs to failed septic systems where gravity flow is not possible, media filters, pressure pipe dosing systems, and other alternatives that would require a separate pump chamber. The Centrifugal STEP System fits into almost any septic tank, and filters the effluent to protect your pump and drainfield components.

FILTER AREA:

- 528 linear feet of 1/16" filtration
- 396 square inches of open area

MATERIALS:

- Tank polyethylene
- Filters polypropylene
- All components are engineered to withstand septic tank environment
- All pump models are cast iron, 1-1/2" discharge, 115 V/1PH submersible pumps with a corrosion-resistant powder coated epoxy finish
- 1-1/4" SCH 40 PVC discharge assemblies (check valve available)
- Pipe seal for discharge pipe included

INSTALLATION:

Install per local codes and National Electrical Code See CL0029 for installation instructions and service parts

EASY MAINTENANCE:


The discharge has a union for easy removal of the pump and floats. The filter handle aids in the removal of the filter pack. Service as needed.

LONG LIFE:


Superior quality components make a superior quality system. Easy to install, maintain, and operate.

• Standard overall height is 46".





© Copyright 2023. All rights reserved. 1



TOTAL DYNAMIC HEADFLOW PER MINUTE EFFLUENT AND DEWATERING

MO	MODEL		51*		53*		98*		142		145		151		152		153	
Feet	Meters	Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters	Gal.	Liters	
5	1.5	18	68	43	163	-	-	18	68	-	-	50	189	-	-	-	-	
10	3.0	13	50	34	129	-	-	18	68	-	-	45	170	-	-	-	-	
15	4.6	8	32	19	72	45	170	18	68	-	-	38	144	-	-	-	-	
20	6.1	2	8	-	-	25	95	17	64	-	-	29	110	44	167	-	-	
25	7.6	-	-	-	-	-	-	16	61	49	186	16	61	34	129	42	159	
30	9.1	-	-	-	-	-	-	14	53	45	171	-	-	23	87	33	125	
40	12.2	-	-	-	-	-	-	7	26	35	133	-	-	-	-	22	85	
50	15.2	-	-	-	-	-	-	1	4	26	99	-	-	-	-	11	42	
60	18.3	-	-	-	-	-	-	-	-	16	61	-	-	-	-	-	-	
Shut-off Head:		21 ft.(6.4m)		19.25 ft.(5.9m)		23 ft.(7.0m)		62 ft.(18.9m)		74 ft.(22.6m)		30 ft. (9.1m)		38 ft. (11.6m)		44 ft. (13.4m)		

* Pump powered by ZMW Zoeller Motor Works motor


Prepackaged Systems (Unassembled)

Centrifugal STEP Packages with Automatic Pumps (BN Models)


5040-0002	Automatic BN51 pkg (1, 4)	
5040-0003	Automatic BN51 w/ alarm pkg (1, 3, 4, 5)	
5040-0004	Automatic BN51 w/ check valve pkg (1, 2, 4)	
5040-0005	Automatic BN51 w/ alarm and check valve pkg (1, 2, 3, 4, 5)	
5040-0018	Automatic BN51 w/ Qwik Box (1, 4, 6)	
5040-0019	Automatic BN51 w/ Qwik Box / alarm system (1, 3, 4, 5, 6)	
5040-0020	Automatic BN51 w/ Qwik Box and check valve pkg (1, 2, 4, 6)	\square
5040-0021	Automatic BN51 w/ Qwik Box / alarm system and check valve pkg (1, 2, 3, 4, 5, 6)	
5040-0029	Automatic BN53 with filter, pump chamber, and pump (1, 4)	
5040-0030	Automatic BN98 with filter, pump chamber, and pump (1, 4)	
5040-0006	Automatic BN142 pkg (1, 4)	
5040-0007	Automatic BN142 w/ alarm pkg (1, 3, 4, 5)	
5040-0008	Automatic BN142 w/ check valve pkg (1, 2, 4)	6 OC
5040-0009	Automatic BN142 w/ alarm and check valve pkg (1, 2, 3, 4, 5)	
5040-0022	Automatic BN142 w/ Qwik Box (1, 4, 6)	Ĭ
5040-0023	Automatic BN142 w/ Qwik Box / alarm system(1, 3, 4, 5, 6)	
5040-0024	Automatic BN142 w/ Qwik Box and check valve pkg (1, 2, 4, 6)	
5040-0025	Automatic BN142 w/ Qwik Box / alarm system and check valve pkg (1, 2, 3, 4, 5, 6)	
5040-0031	Automatic BN145 with filter, pump chamber, and pump	
5040-0032	Automatic BN151 with filter, pump chamber, and pump	ſ
5040-0033	Automatic BN152 with filter, pump chamber, and pump	(ji
5040-0034	Automatic BN153 with filter, pump chamber, and pump Note: A	ll on/of
		,

Centrifugal STEP Packages with Nonautomatic Pumps (N Models)

-	
5040-0010	Nonautomatic N51 pkg (1, 4)
5040-0011	Nonautomatic N51 w/ control panel pkg (1, 3, 4)
5040-0012	Nonautomatic N51 w/ check valve pkg (1, 2, 4)
5040-0013	Nonautomatic N51 w/ control panel and check valve pkg (1 ,2, 3, 4)
5040-0035	Nonautomatic N53 with filter, pump chamber, and pump (1, 4)
5040-0036	Nonautomatic N98 with filter, pump chamber, and pump (1, 4)
5040-0014	Nonautomatic N142 pkg (1, 4)
5040-0015	Nonautomatic N142 w/ control panel pkg (1, 3, 4)
5040-0016	Nonautomatic N142 w/ check valve pkg (1, 2, 4)
5040-0017	Nonautomatic N142 w/ control panel and check valve pkg (1, 2, 3, 4)
5040-0037	Nonautomatic N145 with filter, pump chamber, and pump (1)
5040-0038	Nonautomatic N151 with filter, pump chamber, and pump (1)
5040-0039	Nonautomatic N152 with filter, pump chamber, and pump (1)
5040-0040	Nonautomatic N153 with filter, pump chamber, and pump (1)



All on/off alarm settings must comply with all state and local codes.



Note: It is the responsibility of the installer & designer to assure all state and local codes are met.

Custom Applications

FILTER HANDLE

(A L II 7

SK2031

SK2029

The following is intended to aid selection of the components needed for the widest variety of systems. Prepackaged systems (unassembled) are also available for the most commonly selected systems.


(A) Centrifugal STEP Vault

Includes filter pak with handle and pump chamber preassembled at factory.

- 5040-0001 46" Centrifugal STEP Vault Wgt. 20.0 lbs.
- □ 5040-0026 50" Centrifugal STEP Vault Wgt. 30.0 lbs.
 □ 5040-0027 63" Centrifugal STEP Vault Wgt. 30.0 lbs.
- □ 5040-0041 Centrifugal STEP Vault Stand (page 2)
- □ 5040-0042 46" Centrifugal STEP Vault w/ Stand (page 2)

(C) Discharge Assembly

Discharge pipe assembly consists of a reducer, schedule 40 PVC piping, elbows, flexible PVC pipe, union / ball valve, pipe seal, and 1-1/4" flexible stub to extend outside of riser. Preassembled and welded at the factory.



- □ 170-0083 1-1/4" diameter -Wgt. 4.0 lbs.
- 170-0084 1-1/4" diameter, with check valve - Wgt. 4.0 lbs.

(E) Junction Boxes* / Pre-wired Conduit

Prewired conduits are designed to make the electrical wiring easier. Assemblies come with the correct number of wires of the correct gauge for the application. Junction box is included if needed.

For automatic or float switch control - with or without alarm:

FUI automatic UI I	ioal Switch control - with of without alarm.				
□ 5100-0011	25' long w/J-Box (3 cord seals, 2 plugs) - Wgt. 10 lbs.				
□ 5100-0012	35' long w/J-Box (3 cord seals, 2 plugs) - Wgt. 14 lbs.				
□ 5100-0013	50' long w/J-Box (3 cord seals, 2 plugs) - Wgt. 18 lbs.				
□ 5100-0014	75' long w/J-Box (3 cord seals, 2 plugs) - Wgt. 26 lbs.				
□ 5100-0015	100' long w/J-Box (3 cord seals, 2 plugs) - Wgt. 33 lbs.				
For Qwik Box pump control - with or without alarm:					
□ 5100-0016	25' long - Wgt 10 lbs.				
□ 5100-0017	35' long - Wgt. 12 lbs.				
□ 5100-0018	50' long - Wgt. 16 lbs.				
□ 5100-0019	75' long - Wgt. 24 lbs.				
□ 5100-0020	100' long - Wgt. 31 lbs.				
For control panels	s and nonautomatic pumps:				
□ 5100-0001	25' long w/J-Box (4 cord seals, 1 plug) - Wgt. 10 lbs.				
□ 5100-0002	35' long w/J-Box (4 cord seals, 1 plug) - Wgt. 14 lbs.				
□ 5100-0003	50' long w/J-Box (4 cord seals, 1 plug) - Wgt. 18 lbs.				
□ 5100-0004	75' long w/J-Box (4 cord seals, 1 plug) - Wgt. 26 lbs.				
□ 5100-0005	100' long w/J-Box (4 cord seals, 1 plug) - Wgt. 33 lbs.				
NEMA 4X Junction Boxes:					
Select junction box based on number of cords present in riser.					
□ 10-1030	$4^{\rm "L}x4^{\rm "W}x2^{\rm "H}$ (2 UF & 2 round cord seals-unassembled) - Wgt. 1 lb.				
	4"L x 4"W x 2"H (3 round cord seals, 3/4" hub-				

□ 10-0776	4"L x 4"W x 2"H (3 round cord seals, 3/4" hub- unassembled) - Wgt. 1 lb.
□ 10-1399	4"L x 4"W x 4"H (4 round cord seals, 1-1/2" hub- unassembled) - Wgt. 2 lbs.

* Junction box not required w/ Qwik Box system.

(B) Pump

Pump should be selected based on pump performance. (All other pump models when purchased a la carte must be purchased through an authorized Zoeller Pump Company distributor.)

 115 V Automatic Units (BN)

 □
 51-0006 - Wgt. 28 lbs.

 □
 142-0006 - Wgt. 55 lbs.

 115 V Nonautomatic Units (N)

 □
 51-0002 - Wgt. 27 lbs.

 □
 142-0002 - Wgt. 54 lbs.

(D) Control/Alarm

A high water alarm is recommended and most codes require one. For automatic pumps choose from the following alarm boxes. For nonautomatic pumps, the alarm is integral with control panel.

Qwik Box Control/Alarm System

🗆 10-0579 Qwik Box, 115 V - Wgt. 3 lbs.

□ 10-1359 Qwik Box, 115 V w/ alarm (indoor) - Wgt. 7 lbs.

Indoor/Outdoor Alarm

□ 91104-0001 Alarm System with 15' Float - Wgt. 5 lbs.

- 🗆 10-0744 20' Mechanical Control Switch
- 🗆 10-1877 25' Mechanical Control Switch
- 🗆 10-1874 50' Mechanical Control Switch
- 91104-0003 Alarm System without Float Wgt. 5 lbs.

Controls

10-0125 Simplex Panel, 115/230V, 1Ph, 0-20 Amps, NEMA 4X, 3 Floats - Wgt. 11.5 lbs.

□ 10-0684 Timed Dose Panel 115 V, 1Ph, 0-20 Amps, NEMA 4X, ETM, Cycle Counter, 3 Floats - Wgt. 20 lbs.

Note: All variable level control switches in this section are mechanically activated and do not contain mercury.

(F) Standard Riser Systems

An access riser is required on the outlet of the septic tank for proper installation of the STEP system. Many codes require a locking latch to prevent tampering with the system.



SK1838B

SK2030

24" AccessRiser

	172-0003	24" dia x 1' long - Wgt. 32 lbs.
	172-0044	24" dia x 18" long - Wgt. 39 lbs.
	172-0004	24" dia x 2' long - Wgt. 46 lbs.
	172-0005	24" dia x 3' long - Wgt. 60 lbs.
	172-0019	Adhesive (for mounting in pre-cast groove) quart- Wqt. 1 lb.
	172-0020	Lockable Latch Assembly - Wgt. 2 lb.
	172-0048	Seal Ring - Wgt. 5 lb.
	172-0047	Bolt Down Kit - Wgt. 2 lb.
30'	' Access Rise	r
	172-0029	30" dia x 1' long - Wgt. 59 lbs.
	172-0045	30" dia x 18" long - Wgt. 75 lbs.
	172-0030	30" dia x 2' long - Wgt. 92 lbs.
	172-0031	30" dia x 3' long - Wgt. 125 lbs.
	172-0019	Adhesive (for mounting in pre-cast groove) quart- Wqt. 1 lb.
	172-0056	Lockable Latch Assembly - Wgt. 2 lbs.
	172-0049	Seal Ring - Wgt. 5 lb.
	172-0057	Bolt Down Kit - Wgt. 2 lb.