

Trusted. Tested. Tough.®

SECTION: 2.40.030

FM2491

0122

Supersedes

1014

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
 SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
 TEL: (502) 778-2731 • 1 (800) 928-PUMP • FAX: (502) 774-3624

Visit our website:
 zoellerpumps.com

DIAPHRAGM PRESSURE TANK DRAWDOWN CHARTS

AIR-E-TAINER® PRE-PRESSURIZED WELL SYSTEM TANKS

Part No.	Model No.	Total Tank Volume Gallons	Equiv Standard Pressure Tank***	Drawdown-Gallons by PSI Settings			Approx. Size In. Dia x Ht	Ship Wt. Lbs.	NPT Size/ MTL	Factory Precharge PSIG	Max Working Pressure (PSI)	Max Working Temp
				20/40	30/50	40/60						
10-2367	AT15*	4.5	12	1.7	1.4	1.2	10 x 15	10	3/4"	28	100	140
10-2368	AT44	14	30	5.2	4.3	3.8	16 x 21.8	30	1"	28	100	200
10-2369	AT66	20	42	7.4	6.2	5.4	16 x 28.8	35	1"	28	100	200
10-2370	AT122	33	82	12.3	10.3	9.0	16 x 43	53	1"	28	100	200
10-2371	AT144	44	120	16.3	13.6	11.9	21 x 36.2	66	1-1/4"	38	100	200

* Compact in-line tank

** Horizontal tank with mounting bracket

*** Air-E-Tainer® tanks will deliver drawdown equivalent to conventional tanks of this size.

CAUTION: Install a pressure relief valve on any installation where the pump pressure can exceed the tank's maximum working pressure.



Diaphragm Tank Stand

10-2372 pump stand for mounting jet pumps on top of 10-2368, 10-2369 and 10-2370 Air-E-Tainer® tanks.



10-2372

Check and Foot Valves

Check Valves Spring Controlled for general service of jet, submersible or centrifugal, for horizontal or vertical application.

Foot Valves Spring Controlled for jet or centrifugal pumps. For vertical application.



Brass Check Valves

Order Number	NPT
30-0196	1"
30-0197	1-1/4"
30-0198	1-1/2"



Brass Check Valves

Order Number	NPT
10-2361*	1-1/4"x1"

*Dual purpose 1" ID 1-1/4" OD threaded

Switches and Gauges

Pressure Switches



10-2376/10-2377

Order No.	Switch Setting	Bottom Connection NPT	Maximum Electrical Rating	
			Single Phase	
			115V	230V
10-2376	20-40	1/4 M	1 HP	1-1/2 HP
10-2377	30-50	1/4 M	1-1/2 HP	2 HP
10-2378*	20-40	1/4 F	1 HP	1-1/2 HP

* Indicates low pressure cut off for low yielding wells.
NOTE: All switches are two pole.

Pressure Gauges

Order No.	Max. Pressure	Connection NPT
10-2379	100 PSI	1/4"
10-2380	200 PSI	1/4"



10-2379
10-2380

Submersible Well Pump Accessories



10-2345



10-2344



10-2347



10-2343 (5 per pkg.)

Order No.	Description
10-2343	Cable guards
10-2347*	Pressure Relief Valve, 1/2" NPT, 75 PSI rated
10-2345	Submersible Torque Arrestor
10-2344	Wire Splice Kit

*NOTE: Install a pressure relief valve with any pump capable of producing more than 75 PSI at the tank.

Some models are not for sale in states following Proposition 65 and AB1953. Alternatives are available.



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

Trusted. Tested. Tough.®

Visit our website:
zoellerpumps.com