



# **MODEL 131**

**Drain Pump Series** 

Remove water from areas with no gravity flow





Designed for applications where gravity flow is not possible including laundry tray, wet bar sink, lavatory, air conditioning condensate, and dehumidifier. Can also be used in conjunction with dishwashers and garbage disposals.

### **Features:**


- · Automatic pumps with tank cord seals
- No inlet filters or screens to clean
- Polypropylene basin and lid
- Low profile, easy installation; can be installed in base cabinet under a sink
- Trap can be installed inside basin

## 100% factory tested


### **TOTAL DYNAMIC HEAD FLOW PER MINUTE**


MODELS		104/132		105/ 110/11	/106 15/120	131		
Feet	Meters	Gal.	Liters	Gal.	Liters	Gal.	Liters	
5	1.5	38	144	43	163	72	273	
10	3.0	30	114	34	129	61	231	
15	4.6	14	53	19	72	45	170	
20	6.1					25	95	
Shut-off Head:		18 ft. (5.5m)		19.25 ft. (5.9m)		23 ft. (7.0m)		

009898




#### **INTERNAL TRAP \*\***





#### STANDARD INSTALL



Dehumidifier or Air Conditioner

Applications include: laundry tray pump, wet bar sink, lavatory, air conditioning condensate or dehumidifier water removal. It can also be used in conjunction with dishwashers and garbage disposal applications.

Model	MODEL COMPARISON											
	Seal	Mode	Volts	Ph	Amps	HP	Hz	Lbs	Kg			
104 (M72)	Single	Auto	115	1	3.1	1/3	60	16	7			
105 (M53)	Single	Auto	115	1	9.7	3/10	60	30	14			
106 (M63)	Single	Auto	115	1	9.7	3/10	60	36	16			
110 (M55)	Single	Auto	115	1	9.7	3/10	60	32	15			
115 (M57)	Single	Auto	115	1	9.7	3/10	60	36	16			
120 (M59)	Single	Auto	115	1	9.7	1/3	60	37	17			
132 (M72)	Single	Auto	115	1	3.1	1/3	60	19	9			
131 (M98)	Single	Auto	115	1	9.4	1/2	60	43	20			







FM3164 0224 Supersedes 0823